



DIESEL DISPENSING STATION HDM 50 PRO LZ

Article number: 110600340
EAN: 4031109005135

DESCRIPTION

- Liter counter
- Interface: single pulse
- TRbF compliant, incl. drip tray and leak monitoring
- Gear pump with gas separator, filter
- 4-piston meter with pulse generator
- Type-approved automatic nozzle A 2010, incl. swivel

Use the functions on the website to remember or compare

- Optional hose mast
- Nozzle holder
- Rear and underground suction pipe
- Suction pipe min. DN 40
- Robust powder-coated sheet steel housing
- 5-digit segment display

*Depending on viscosity and system

TECHNICAL DETAILS

Flow rate	50*/min
Ambient temperature	-25 - +55°C
Medium temperature	-10 - +35°C
Driving power	1100W
Power supply (electrical voltage)	400V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 25 x 4 m
Viscosity range	1-20mPa·s
Display	640 x 480 px
Accuracy	< 0,5%
Connection suction side	DN 40
Suction height	max. 4000*

Use the functions on the website to remember or compare

EQUIPMENT

233400406	Dispensing hose, with inlay, 6.00 m DN 19 x 4 instead of 4.00 m DN 19 x 4
233400408	Dispensing hose, with inlay, 8.00 m DN 19 x 4 instead of 4.00 m DN 19 x 4
233400182	Angle check valve 1 1/4" HDM 80 eco and pro
233400188	Angle check valve 1 1/4" for underground tanks
233400165	Floating switch HDM eco and pro
233400325	Host mast for HDM pro
816898013	Return line adapter PU hose to 1/4"
233400300	Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA
233400370	Foundation frame B 550

Use the functions on the website to remember or compare