



DIESEL DISPENSING STATION HDM 150 PRO LZ

Article number: 110600540
EAN: 4031109005197

DESCRIPTION

- Liter counter
- Interface: single pulse
- TRbF compliant, incl. drip tray and leak monitoring□
- Two gear pump with gas separator, filter□
- 2x 4-piston meter with pulse generator□
- Type-approved automatic nozzle ZVA 25 / ZVA 19, incl. swivel□

Use the functions on the website to remember or compare

- Optional hose mast□
- Nozzle holder□
- Rear and underground suction pipe□
- Suction pipe min. DN 50□
- Robust powder-coated sheet steel housing□
- 5-digit segment display

*Depending on viscosity and system

TECHNICAL DETAILS

Flow rate	140*/min
Ambient temperature	-25 - +55°C
Medium temperature	-10 - +35°C
Driving power	2200W
Power supply (electrical voltage)	400V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 25 x 4 m / DN 19 x 4 mm
Max. operating pressure	2bar
Viscosity range	1-20mPa·s
Delivery pressure	2bar
Display	640 x 480 px
Air pressure max.	3,5bar
Accuracy	< 0,5%

Use the functions on the website to remember or compare

Connection suction side

DN 50mm

Suction height

max. 4000*mm

EQUIPMENT

233400506

Dispensing hose, with inlay 6.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4

233400508

Dispensing hose 8.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4

233400184

Angle check valve 2" HDM 150 pro / HDM 150/50 pro

233400165

Floating switch HDM eco and pro

233400325

Host mast for HDM pro

816898013

Return line adapter PU hose to 1/4"

233400300

Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA

233400371

Foundation frame B 850

Use the functions on the website to remember or compare