



DIESEL DISPENSING STATION HDM 60 eco LZ

Article number: 110700865
EAN: 4031109004992

DESCRIPTION

- With liter counter
- Conforms to the Technical Rules Concerning Flammable Liquids (TRbF), incl. drip tray and leakage monitoring
- Rotary vane pump with single-phase asynchronous motor
- Oval gear counter with pulse generator
- Interface: double pulse
- A 2010 automatic nozzle with approved design, incl. swivel joint

Use the functions on the website to remember or compare

- Discharge hose holder
- Rear and underground suction pipe connection possible
- Suction pipe min. DN 32
- Robust, powder-coated sheet steel housing
- Background illuminated LC display

* depends on viscosity and system

TECHNICAL DETAILS

Flow rate	55l/min
Ambient temperature	-20 - +55°C
Medium temperature	-10 - +35°C
Suction hose	DN 25
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 19 x 4 m
Impulses	100Impulse/l
Tap count	1
Accuracy	± 0,5%
Connection suction side	G 1"
Suction height	3,5m

Use the functions on the website to remember or compare

EQUIPMENT

233400406	Dispensing hose, with inlay, 6.00 m DN 19 x 4 instead of 4.00 m DN 19 x 4
233400408	Dispensing hose, with inlay, 8.00 m DN 19 x 4 instead of 4.00 m DN 19 x 4
233400181	Angle check valve 1" HDM 60 eco
233400195	Mounting kit return line for HDM eco
233400187	Angle check valve 1" HDM 60 eco
233400165	Floating switch HDM eco and pro
233400180	Filter bracket incl. 30 microfilter cartridge
233400300	Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA
233400373	Foundation frame HDM eco

Use the functions on the website to remember or compare