



BIODIESEL DISPENSER HDM 60 eco LZ BIO

Article number: 110700876
EAN: 4031109020268

DESCRIPTION

Dispenser with litre counter

Safety features:

- incl. drip tray
- incl. leakage monitoring

Use the functions on the website to remember or compare

Technical details:

- Version: not calibratable
- Pump: rotary vane pump W 50 II with asynchronous motor
- Metering principle: oval gear meter with pulser
- discharge hose: 4m DN 19 NBR with type-approved automatic nozzle ZVA 25, discharge hose holder
- Housing: robust powder-coated steel housing
- Display: illuminated
- Medium: Biodiesel conform with EN 14214

TECHNICAL DETAILS

Flow rate	55l/min
Ambient temperature	-20 - +55°C
Medium temperature	-10 - +35°C
Suction hose	DN 25
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 19 x 4 m
Display	LCD-Digitalanzeige, beleuchtet
Tap count	1
Accuracy	± 0,5%
Connection suction side	G 1"
Suction height	3,5m

Use the functions on the website to remember or compare

EQUIPMENT

233400181	Angle check valve 1" HDM 60 eco
233400195	Mounting kit return line for HDM eco
233400187	Angle check valve 1" HDM 60 eco
233400165	Floating switch HDM eco and pro
233400373	Foundation frame HDM eco
233400409	Dispensing hose Biodiesel, with inlay, 8.00 m DN 19 x 4 instead of 4.00 m DN 19 x 4
233400177	Biodiesel Filter incl. bracket 1"

Use the functions on the website to remember or compare