



ELECTRICAL OIL EXTRACTOR FOR OIL DISPOSAL STATIONARY, WITHOUT ACCESSORIES

Article number:013873013

EAN: 4031109006422

DESCRIPTION

- For engine oil, gear oil, hydraulic oil and radiator antifreeze (concentrate)
- 300 Åµ filtering screen
- Vacuum controlled automatic switch-off with set overrun time

Use the functions on the website to remember or compare

- Vacuum display
- Non-return valve
- Separate start button
- Auf Mounted on a bracket

TECHNICAL DETAILS

Flow rate	ca. 22l/min
Driving power	0,55kW
Protection class	IP 54
Power supply (electrical voltage)	400V
Power supply (electrical frequency)	50Hz
Viscosity range	max. 2000mPa-s
Delivery pressure	max. 5bar
Pressure connection female thread	3/4"
Suction connection female thread	3/4"

EQUIPMENT

027028700	Dust cover for suction used oil pump
026090511	Flex pipe DN 20 x 500 mm long
027133582	2-way ball valve G 3/4 i+a G 3/4" ia

Use the functions on the website to remember or compare

027270501	Extraction fitting, Mercedes Benz 1/2
027027600	Special Daimler suction probe Ø 8.2 mm, 1000 mm long, flexible
027027610	Suction probe 5,4 mm, 940 mm long, flexible
027027620	Suction probe 8,0 mm, 950 mm long, flexible
027027630	Suction probe 5,4 mm, 1.200 mm long, flexible
027095102	Probe quiver for wall mounting long
043332351	Hose wall holder, cast aluminum
029060432	Suction and dispensing hose DN 16, 3.15 m, G 1/2" external thread
406505790	Reducing nipple 3/4"male - 1/2" female, galvanized
043561011	Drip pan, single piece, with drainage screw one piece

Use the functions on the website to remember or compare