

TANK-MOUNTED UNIT TE 2NE 1500 L, ELECTRIC, FOR COMMERCIAL USE

RADIATOR ANTIFREEZE R

OIL O

Article number:015417111

EAN: 4031109016735

DESCRIPTION

- PE-combi storage tank, double walled, level display. Pallet feet for pallet truck or fork lift.
- internal gear pump

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- full hose system with pressure switch and time controlled safety shutdown.
- hose reel eco, closed, with 10 m dispensing hose
- hand flow meter FMOG, digital
- *the legally prescribed, approved overfill protection device design is in the optional cultivable safety tank accessory set contained.*

TECHNICAL DETAILS

Flow rate	10l/min
Driving power	0,55kW
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Tank capacity	1500l
Viscosity range	max. 2000mPa·s
Delivery pressure	max. 10bar
Output hose	10 m

TECALEMIT GMBH & CO. KG
Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock