



## DOUBLE MEMBRANE PUMP 1/2 WITH VACUUM CONTROL

Article number: 015433225

EAN:

DIESEL / FUEL OIL **D**  
RADIATOR ANTIFREEZE **R**  
OIL **O**  
USED OIL **O**

## DESCRIPTION

Compressed air double membrane pump incl. vacuum control for Diesel, motor, gear and hydraulic oil,

Use the functions on the website to remember or compare

antifreeze concentrate, used oil of known origin and used antifreeze.

## TECHNICAL DETAILS

|                                         |                |
|-----------------------------------------|----------------|
| Flow rate                               | ca. 20l/min    |
| Protection class                        | IP 54          |
| Power supply (electrical voltage)       | 230V           |
| Power supply (electrical frequency)     | 50Hz           |
| Viscosity range                         | max. 2000mPa·s |
| Pressure connection female thread       | 1/2"           |
| Suction connection female thread        | 1/2"           |
| Air pressure max.                       | 7,5bar         |
| Air consumption                         | 400l/min       |
| Dirt particle size max.                 | 1,6mm          |
| Compressed air connection female thread | 1/4"           |

## EQUIPMENT

|           |                                                                     |
|-----------|---------------------------------------------------------------------|
| 029056451 | Suction line for 200 lt. drum G 3/4" DN32, flexible for 200lt. drum |
| 026090511 | Flex pipe DN 20 x 500 mm long                                       |

Use the functions on the website to remember or compare

|                  |                                                                                  |
|------------------|----------------------------------------------------------------------------------|
| <b>027133582</b> | 2-way ball valve G 3/4 i+a G 3/4" ia                                             |
| <b>029056541</b> | Suction hose DN 32, 4.50 m                                                       |
| <b>027027551</b> | Suction pipe DN 28, 800 mm DN 28, 800 mm                                         |
| <b>029056361</b> | Dispensing hose DN 32, 4.5 m DN 32, 4.50 m                                       |
| <b>029060412</b> | Suction and dispensing hose DN 16, 1.60 m, G 1/2" external thread                |
| <b>029060422</b> | Suction and dispensing hose DN 16, 2.25 m, G 1/2" external thread                |
| <b>029060432</b> | Suction and dispensing hose DN 16, 3.15 m, G 1/2" external thread                |
| <b>029060442</b> | Suction and dispensing hose DN 16, 4.50 m, G 1/2" external thread                |
| <b>029060462</b> | Suction and dispensing hose DN 16, 6.30 m, G 1/2" external thread                |
| <b>020202881</b> | Automatic pump switch-off, time controlled time controlled                       |
| <b>043332351</b> | Hose wall holder, cast aluminum                                                  |
| <b>027270011</b> | Extraction fitting, compl.                                                       |
| <b>027270501</b> | Extraction fitting, Mercedes Benz 1/2                                            |
| <b>027028011</b> | Combined MB / VAG Adapter                                                        |
| <b>043561011</b> | Drip pan, single piece, with drainage screw one piece                            |
| <b>027027011</b> | Suction probe, 5 mm, 645 mm long, rigid, white 5 mm, 645 mm long, rigid, white   |
| <b>027027021</b> | Suction probe, 6 mm, 645 mm long, rigid, yellow 6 mm, 645 mm long, rigid, yellow |

Use the functions on the website to remember or compare

|                  |                                                                              |
|------------------|------------------------------------------------------------------------------|
| <b>027027061</b> | Suction probe, 5.4 mm, 1200 mm long, flexible 5,4 mm, 1200 mm long, flexible |
| <b>027027072</b> | Suction probe, 8 mm, 700 mm long, flexible 8 mm, 700 mm long, flexible       |
| <b>027027141</b> | Suction probe, 5.4 mm, 950 mm long, flexible for MCC-Smart                   |
| <b>041719421</b> | Extraction adapter with pin DN 20 - G3/4"i                                   |
| <b>027027081</b> | Suction probe, 8 mm, 1200 mm long, flexible 8 mm, 1200 mm long, flexible     |
| <b>043711282</b> | Connection bend with pin                                                     |
| <b>027027421</b> | Suction probe Ø 6 mm, 660 mm long, rigid                                     |
| <b>027027411</b> | Suction probe Ø 7.5 mm, 660 mm long, flexible                                |
| <b>027027431</b> | Suction probe Ø 5.4 mm, 950 mm long, flexible                                |
| <b>027027600</b> | Special Daimler suction probe Ø 8.2 mm, 1000 mm long, flexible               |
| <b>043526801</b> | Drip pan for remote oil equipment                                            |
| <b>027270201</b> | Adapter NAG2                                                                 |
| <b>027028600</b> | Adapter plate for oil extractor                                              |
| <b>027027610</b> | Suction probe 5,4 mm, 940 mm long, flexible                                  |
| <b>027027620</b> | Suction probe 8,0 mm, 950 mm long, flexible                                  |
| <b>027027630</b> | Suction probe 5,4 mm, 1.200 mm long, flexible                                |
| <b>027028700</b> | Dust cover for suction used oil pump                                         |
| <b>027095102</b> | Prove quiver for wall mounting long                                          |
| <b>029056542</b> | Suction hose DN 32 2.0m long, with coupling                                  |

Use the functions on the website to remember or compare

**027270301**

Filling Adapter NAG2 eco

Use the functions on the website to remember or compare

**TECALEMIT GMBH & CO. KG**Am Heizwerk 4  
24983 Handewitt**T** +49 461 8696-126  
**M** [sales@tecalemit.de](mailto:sales@tecalemit.de)mo-th: 08:00 - 16:30 o'clock  
fr: 08:00 - 15:00 o'clock