



ELECTRIC PUMP TECPUMP 600 AC, STANDARD, 4 M DISCHARGE HOSE

Article number: 105620400

EAN: 4031109012812

DIESEL / FUEL OIL



RADIATOR ANTIFREEZE



DESCRIPTION

- For diesel, heating oil EL/L, and radiator antifreeze (concentrate), GTL, HVO and R33
- Self-priming with integrated siphon protection

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- With integrated filter on the suction side
- A 2010 automatic nozzle with hose swivel joint
- 4 m discharge hose
- 1,6 m suction hose
- Schuko mains plug - cable length 2 m

TECHNICAL DETAILS

Flow rate	ca. 55l/min
Drum thread	G 2"
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	370W
Protection class	IP 54
Suction hose	1600mm
Current consumption	2,6A
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	4m
Dispense hose profile	DN 19 x 4mm
Max. suction height	4m
Delivery pressure	max. 2bar
Suction connection	G 1"

Use the functions on the website to remember or compare

Cable length

2m

EQUIPMENT

252300000	Standard nozzle ZV 2000
252690000	Automatic nozzle ZVA 4.1 Slimline DN 20
234338000	Suction hose for W50II, DN 19 x 4
331000400	Hose DN 19 x 4, G 1 AG, integrated
331000600	Hose DN 19 x 4, G 1 AG, integrated
331000800	Hose DN 19 x 4, G 1 AG, integrated
252620000	Automatic nozzle A 2010
253010101	Mechanical roller counter Z 400, with mounting kit for HORNET 50/80
253591004	Electronic flow meter FMT 3 - POM - add-on kit for HORNET 50/80
253591998	Attachment kit FMT 3 to HORNET 50/80
208600010	Anschlussflansch-Set für TecPump 600

Use the functions on the website to remember or compare