



ELECTRIC PUMP TECPUMP 600 AC FMT 3, STANDARD, 8 M DISCHARGE HOSE

Article number: 105622800

EAN: 4031109013123

DIESEL / FUEL OIL



RADIATOR ANTIFREEZE



DESCRIPTION

- For diesel, heating oil EL/L, and radiator antifreeze (concentrate), GTL, HVO and R33
- Self-priming with integrated siphon protection

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- With integrated filter on the suction side
- Automatic nozzle A 2010 incl. hose swivel joint
- With electronic flow meter FMT 3
- 8 m discharge hose
- 1,6 m suction hose
- Schuko mains plug - cable length 2 m

TECHNICAL DETAILS

Flow rate	ca. 55l/min
Drum thread	G 2"
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	370W
Protection class	IP 54
Suction hose	1600mm
Current consumption	4,5A
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	8m
Dispense hose profile	DN 19 x 4mm
Max. suction height	4m
Delivery pressure	max. 2bar

Use the functions on the website to remember or compare

Suction connection	G 1"
Cable length	2m

Use the functions on the website to remember or compare