



ELECTRIC PUMP TecPump 400 DC 12 STANDARD DESIGN INCL. SIPHON PROTECTION 6 M PUMP HOSE, A2010

Article number: 105710600
EAN: 4031109020008

DESCRIPTION

- Electrically powered self-priming vane pump.
- For conveying diesel, heating oil and radiator antifreeze concentrate, GTL, HVO and R33.
- Ideal for use in agriculture, industry, mobile company filling stations and similar facilities.

Use the functions on the website to remember or compare

- Often used in mobile tank systems for refuelling on building sites and in fields.

Delivery contents:

- Vane pump TecPump 400 DC
- Siphon protection/return flow
- Stainless steel suction filter integrated into the pump chamber
Integrated overflow valve
Connection cable (6 m long) with battery terminals Suction hose: 1,65 m, Pressure hose: 6,0 m
- Automatic pump nozzle A 2010

Technical information:

- Suction filter: Mesh size 0,9 mm
- Duty cycle: 50% ED S2 30 min

TECHNICAL DETAILS

| | |
|-----------------------------------|--------------|
| Flow rate | max. 42l/min |
| Ambient temperature | -20 - +40°C |
| Medium temperature | -10 - +40°C |
| Driving power | 330W |
| Protection class | IP 54 |
| Current consumption | 24A |
| Max. suction height | 4m |
| Delivery pressure | max. 1,2bar |
| Cable length | 6m |
| Pressure connection female thread | G1" |
| Suction connection female thread | G1" |

Use the functions on the website to remember or compare

Power supply (electrical voltage)

12,5V (DC)

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Munketoft 42
24937 Flensburg

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 17:00 o'clock
fr: 08:00 - 15:00 o'clock