



ELECTRIC PUMP TECPUMP 400 DC 24 WITHOUT ACCESSORIES EXCLUDING SIPHON PROTECTION

Article number: 105800100 EAN: 4031109020121

DESCRIPTION

- Electrically powered self-priming vane pump.
- For conveying diesel, heating oil and radiator antifreeze concentrate, GTL, HVO and R33.
- $\bullet \ \ \text{Ideal for use in agriculture, industry, mobile company filling stations and similar facilities}.$

Use the functions on the website to remember or compare

mo-th: 08:00 - 17:00 o'clock fr: 08:00 - 15:00 o'clock



• Often used in mobile tank systems for refuelling on building sites and in fields.

Delivery contents:

- Vane pump TecPump 400 DC
- Stainless steel suction filter integrated into the pump chamber
- Integrated overflow valve
- Connection cable (6 m long) with battery terminals

Technical information:

• Pump type: Vane pump

Suction filter: Mesh size 0,9 mmDuty cycle: 50% ED S2 30 min

TECHNICAL DETAILS

Flow rate	max. 42I/min
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	330W
Protection class	IP 54
Current consumption	13A
Max. suction height	4m
Delivery pressure	max. 1,2bar
Cable length	6m
Pressure connection female thread	G1"
Suction connection female thread	G1"

Use the functions on the website to remember or compare

mo-th: 08:00 - 17:00 o'clock fr: 08:00 - 15:00 o'clock



Power supply (electrical voltage)

24,5V (DC)

Use the functions on the website to remember or compare

 T +49 461 8696-126
 mo-th: 08:00 - 17:00 o'clock

 M sales@tecalemit.de
 fr: 08:00 - 15:00 o'clock