



ELECTRIC PUMP TECPUMP 400 DC 24 STANDARD DESIGN INCL. SIPHON PROTECTION 6 M PUMP HOSE, A2010

Article number: 105810600 EAN: 4031109020145

DESCRIPTION

- Electrically powered self-priming vane pump.
- For conveying diesel, heating oil and radiator antifreeze concentrate, GTL, HVO and R33.
- $\bullet \ \ \text{Ideal for use in agriculture, industry, mobile company filling stations and similar facilities}.$

Use the functions on the website to remember or compare

mo-th: 08:00 - 17:00 o'clock fr: 08:00 - 15:00 o'clock



• Often used in mobile tank systems for refuelling on building sites and in fields.

Delivery contents:

- Vane pump TecPump 400 DC
- Siphon protection/return flow
- Stainless steel suction filter integrated into the pump chamber Integrated overflow valve
 Connection cable (6 m long) with battery terminals Suction hose: 1,65 m, Pressure hose: 6,0 m
- Automatic pump nozzle A 2010

Technical information:

Suction filter: Mesh size 0,9 mmDuty cycle: 50% ED S2 30 min

TECHNICAL DETAILS

Flow rate	max. 42l/min
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	330W
Protection class	IP 54
Current consumption	13A
Max. suction height	4m
Delivery pressure	max. 1,2bar
Cable length	6m
Pressure connection female thread	G1"
Suction connection female thread	G1"

Use the functions on the website to remember or compare

mo-th: 08:00 - 17:00 o'clock fr: 08:00 - 15:00 o'clock



Power supply (electrical voltage)

24,5V (DC)

Use the functions on the website to remember or compare

 T +49 461 8696-126
 mo-th: 08:00 - 17:00 o'clock

 M sales@tecalemit.de
 fr: 08:00 - 15:00 o'clock