



ELECTRIC PUMP TECPUMP 400 DC 24 STANDARD INCL. SIPHON PROTECTION 8 M PUMP HOSE, A2010

Article number: 105810800

EAN: 4031109020152

DIESEL **D**
FUEL OIL
RADIATOR ANTIFREEZE **R**

DESCRIPTION

- Electrically powered self-priming vane pump.

Use the functions on the website to remember or compare

- For conveying diesel, heating oil and radiator antifreeze concentrate, GTL, HVO and R33.
- Ideal for use in agriculture, industry, mobile company filling stations and similar facilities.
- Often used in mobile tank systems for refuelling on building sites and in fields.

Delivery contents:

- Vane pump TecPump 400 DC
- Siphon protection/return flow
- Stainless steel suction filter integrated into the pump chamber
- Integrated overflow valve
- Connection cable (6 m long) with battery terminals Suction hose: 1,65 m, Pressure hose: 8,0 m
- Automatic pump nozzle A 2010

Technical information:

- Suction filter: Mesh size 0,9 mm
- Duty cycle: 50% ED S2 30 min

TECHNICAL DETAILS

Flow rate	max. 42l/min
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	330W
Protection class	IP 54
Current consumption	13A
Max. suction height	4m
Delivery pressure	max. 1,2bar
Cable length	6m

Use the functions on the website to remember or compare

Pressure connection female thread	G1"
Suction connection female thread	G1"
Power supply (electrical voltage)	24,5V (DC)

SPARE PARTS

252300000	Standard nozzle ZV 2000
234338000	Suction hose for W50II, DN 19 x 4
331000800	Hose DN 19 x 4, G 1 AG, integrated
517590011	Schmutzsieb TecPump 400 DC Flügel 5x inkl. O-Ring

Use the functions on the website to remember or compare