



ELECTRIC PUMP TecPump 400 DC 24 STANDARD DESIGN INCL. SIPHON PROTECTION 8 M PUMP HOSE, A2010

Article number: 105820400
EAN: 4031109020169

DESCRIPTION

- Electrically powered self-priming vane pump.
- For conveying diesel, heating oil and radiator antifreeze concentrate, GTL, HVO and R33.
- Ideal for use in agriculture, industry, mobile company filling stations and similar facilities.

Use the functions on the website to remember or compare

- Often used in mobile tank systems for refuelling on building sites and in fields.

Delivery contents:

- Vane pump TecPump 400 DC
- Siphon protection/return flow
- Stainless steel suction filter integrated into the pump chamber
- Integrated overflow valve
- Connection cable (6 m long) with battery terminals Suction hose: 1,65 m, Pressure hose: 8,0 m
- Automatic pump nozzle A 2010

Technical information:

- Suction filter: Mesh size 0,9 mm
- Duty cycle: 50% ED S2 30 min

TECHNICAL DETAILS

Flow rate	max. 42l/min
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	330W
Protection class	IP 54
Current consumption	13A
Max. suction height	4m
Delivery pressure	max. 1,2bar
Cable length	6m
Pressure connection female thread	G1"

Use the functions on the website to remember or compare

Suction connection female thread	G1"
Power supply (electrical voltage)	24,5V (DC)

EQUIPMENT

331000400	Hose DN 19 x 4, G 1 AG, integrated
331000600	Hose DN 19 x 4, G 1 AG, integrated
331000800	Hose DN 19 x 4, G 1 AG, integrated
234338000	Suction hose for W50II, DN 19 x 4
253010101	Mechanical roller counter Z 400, with mounting kit for HORNET 50/80
253591004	Electronic flow meter FMT 3 - POM - add-on kit for HORNET 50/80
252300000	Standard nozzle ZV 2000
252620000	Automatic nozzle A 2010
252690000	Automatic nozzle ZVA 4.1 Slimline DN 20
208600010	Anschlussflansch-Set für TecPump 600
253591998	Attachment kit FMT 3 to HORNET 50/80

Use the functions on the website to remember or compare