HDM ECO ADBLUE® DISPENSER INDOOR, USB MODE

UREA U

Article number:109240000
EAN: 4031109024235

DESCRIPTION

The dispenser is only suitable for indoor insallations and follows rules TRWS 781-2, as it has no hose mast. Precautions must be taken on site to ensure local compliance to meet water protection requirements. This can, for example, be a collecting tray the size of a maximum possible delivery quantity per dispensing or a automatic hose retraction to the hall ceiling.

TECALEMIT GMBH & CO. KG
Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

Description:

- AdBlue dispenser with self-priming pump and automate HDA eco.
- Identification via transponder technology and/or PIN-code.
- Easy data transfer with USB stick via USB interface.
- You can connect the HDA eco to myTecalemit cloud solution, basic version is free. Your tank data are always available, anywhere, anytime. Register and create an account on www.mytecalemit.com to start. It can be used on PC, tablet, Mac and Smartphones.

Caracteristics:

- Non-calibratable
- Tank automat with PC software (4.000 users)
- Double identification system - driver/vehicle
- Identification via transponder technology
- USB included as standard
- TRbF compliant, incl.drip tray and leak monitoring
- Hybrid pump HORNET W 85 H INOX
- Oval gear meter with pulse generator
- Type-approved automatic nozzle A 2003 ES, incl. swivel
- Nozzle holder
- Rear and underground suction pipe connection possible
- Suction line min. DN 25
- Sturdy powder-coated sheet steel housing
- Backlit graphic display
- Stores up to 20.000 tank dispensation data entries
- Data connection via LAN & LTE optionally available
- Menue available selectable in German, English and French
- Additional languages can be installed with a USB flash drive

* Depending on viscosity and system

Your advantages:

- Complete documentation on refueling data
- Access to myTecalemit websoftware
- Service-friendly system structure with prepared return line connection
- User identifikation (driver and/or vehicles) with PIN-code or RFID-transponder possible
- Emergency operation function
- Scallable equipment, also retrofittable

Recommendations:

TECALEMIT GMBH & CO. KG
Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

Please also think about your safety accessories !
Valves, pressure reliefs, filter etc. can be found accordingly in the HDM eco accessories list.

TECHNICAL DETAILS

Flow rate	max. 40l/min
Ambient temperature	-7° - +40°°C
Medium temperature	-7° - +40°°C
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 19 x 4 m
Suction connection female thread	G 1" (BSP)
Tap count	1
Accuracy	± 0,5%
Suction height	4m

EQUIPMENT

224070000	1" mounting set for standard level probes
224061000	Terminal box IP 66 with breathable filter
233400200	Transponder fob for contactless identification of users RFID Tag Type 1

TECALEMIT GMBH & CO. KG
Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

233400373	Foundation frame HDM eco
233400160	Connection for fill level probe
233400081	USB RFID Reader Type 1 USB RFID Reader Type 1
233400506	Dispensing hose, with inlay 6.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4
233400508	Dispensing hose 8.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4
233400181	Angle check valve 1" HDM 60 eco
233400032	LAN connection for HDM eco, HDM eco Box
233400035	WLAN connection for HDM eco, HDM eco Box, HDM eco DEF, HDA eco Box
227702050	Support | In-house Softwarekonfiguration für bis zu 50 Fahrer/Fahrzeuge
227702100	Support | In-house Softwarekonfiguration für bis zu 100 Fahrer/Fahrzeuge
227702500	Support In-house software preconfiguration for up to 50 drivers/vehicles
227702800	Support Software commissioning and initial training
227702900	Support Software commissioning and initial training on site
233400202	RFID - Transponder card RFID Card Type 1
224020020	Füllstandsonde 300 mbar 1,0 %, 4-20mA, 5m Kabel
233400024	LTE module for HDM/HDA eco including SIM card

TECALEMIT GMBH & CO. KG
Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock