



DIESEL FUEL TANK SYSTEM HDT- TECPUMP 600 AC VT 1000

Article number: 110320400

EAN: 4031109013130

DIESEL **D**
FUEL OIL
RADIATOR ANTIFREEZE **R**

DESCRIPTION

- For diesel, heating oil EL/L, and radiator antifreeze (concentrate), GTL, HVO and R33
- Double-walled 1,000 l steel tank made of PE, with bracket

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Munketoft 42
24937 Flensburg

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- Level and optical leak indicator
- Incl. Automatic nozzle A 2010 incl. hose swivel joint
- With integrated filter on the suction side
- Self-priming with integrated siphon protection
- 4 m dispensing hose
- Schuko mains plug - cable length 2 m

TECHNICAL DETAILS

Flow rate	ca. 55l/min
Drum thread	G 2"
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Driving power	370W
Protection class	IP 54
Suction hose	1600mm
Current consumption	2,6A
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	4m
Dispense hose profile	DN 19 x 4mm
Max. suction height	4m
Delivery pressure	max. 2bar

Use the functions on the website to remember or compare

Suction connection	G 1"
Cable length	2m

EQUIPMENT

252300000	Standard nozzle ZV 2000
252690000	Automatic nozzle ZVA 4.1 Slimline DN 20
234338000	Suction hose for W50II, DN 19 x 4
331000400	Hose DN 19 x 4, G 1 AG, integrated
331000600	Hose DN 19 x 4, G 1 AG, integrated
331000800	Hose DN 19 x 4, G 1 AG, integrated
252620000	Automatic nozzle A 2010
253010101	Mechanical roller counter Z 400, with mounting kit for HORNET 50/80
253591004	Electronic flow meter FMT 3 - POM - add-on kit for HORNET 50/80
253591998	Attachment kit FMT 3 to HORNET 50/80

Use the functions on the website to remember or compare