



DIESEL DISPENSING STATION HDM 150/050 PRO LZ

DIESEL / FUEL OIL **D**

Article number: 110600640

EAN: 4031109005227

DESCRIPTION

- Liter counter
- Interface: single pulse
- TRbF compliant, incl. drip tray and leak monitoring

Use the functions on the website to remember or compare

- Two gear pumps with gas separator, filter
- 2x 4-piston meter with pulse generator
- Type-approved automatic nozzle ZVA 25 / ZVA 19, incl. swivel
- Optional hose mast
- Nozzle holder
- Rear and underground suction pipe
- Suction pipe min. DN 50
- Robust powder-coated sheet steel housing
- 5-digit segment display

*Depending on viscosity and system

TECHNICAL DETAILS

Flow rate	140 / 50*l/min
Ambient temperature	-25 - +55°C
Medium temperature	-10 - +35°C
Driving power	2200W
Power supply (electrical voltage)	400V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 25 x 4 m / DN 19 x 4 mm
Viscosity range	1-20mPa·s
Display	640 x 480 px
Accuracy	< 0,5%
Connection suction side	DN 50
Suction height	max. 4000*mm

Use the functions on the website to remember or compare

EQUIPMENT

233400371	Foundation frame B 850
233400165	Floating switch HDM eco and pro
233400506	Dispensing hose, with inlay 6.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4
233400508	Dispensing hose 8.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4
233400325	Host mast for HDM pro
233400184	Angle check valve 2" HDM 150 pro / HDM 150/50 pro
233400300	Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA
816898013	Return line adapter PU hose to 1/4"

Use the functions on the website to remember or compare