



DIESEL DISPENSING STATION HDM 80 ECO LZ

DIESEL **D**

Article number: 110700885

EAN: 4031109005029

DESCRIPTION

- With liter counter
- Conforms to the Technical Rules Concerning Flammable Liquids (TRbF), incl. drip tray and leakage monitoring
- Rotary vane pump with single-phase asynchronous motor

Use the functions on the website to remember or compare

- Oval gear counter with pulse generator
- Interface: double pulse
- A 2010 automatic nozzle with approved design, incl. swivel joint
- Discharge hose holder
- Rear and underground suction pipe connection possible
- Suction pipe min. DN 50
- Robust, powder-coated sheet steel housing
- Background illuminated LC display

* depends on viscosity and system

TECHNICAL DETAILS

Flow rate	75l/min
Ambient temperature	-20 - +55°C
Medium temperature	-10 - +35°C
Suction hose	DN 32
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 25 x 4 m
Impulses	100Impulse/l
Suction connection	DN 50
Tap count	1
Accuracy	± 0,5%
Connection suction side	G 1 1/4"

Use the functions on the website to remember or compare

Suction height

3,5m

EQUIPMENT

233400165

Floating switch HDM eco and pro

233400373

Foundation frame HDM eco

234348001

Suction hose HDM 80 eco Box

233400186

Slanted seat filter for G 1 1/4 for HDM 80 eco Box

233400506Dispensing hose, with inlay 6.00 m DN 25 x 4
instead of 4.00 m DN 25 x 4**233400508**Dispensing hose 8.00 m DN 25 x 4 instead of 4.00 m
DN 25 x 4**233400182**

Angle check valve 1 1/4" HDM 80 eco and pro

233400188

Angle check valve 1 1/4" for underground tanks

233400195

Mounting kit return line for HDM eco

233400180

Filter bracket incl. 30 microfilter cartridge

233400300Surcharge fee for Slimline ZVA dispensing nozzle
instead of TECALEMIT ZVA

Use the functions on the website to remember or compare