



DIESEL DISPENSING STATION HDM 80 ECO LZ

DIESEL / FUEL OIL **D**

Article number: 110700885

EAN: 4031109005029

DESCRIPTION

- With liter counter
- Conforms to the Technical Rules Concerning Flammable Liquids (TRbF), incl. drip tray and leakage monitoring
- Rotary vane pump with single-phase asynchronous motor

Use the functions on the website to remember or compare

- Oval gear counter with pulse generator
- Interface: double pulse
- A 2010 automatic nozzle with approved design, incl. swivel joint
- Discharge hose holder
- Rear and underground suction pipe connection possible
- Suction pipe min. DN 50
- Robust, powder-coated sheet steel housing
- Background illuminated LC display

* depends on viscosity and system

TECHNICAL DETAILS

Flow rate	75l/min
Ambient temperature	-20 - +55°C
Medium temperature	-10 - +35°C
Suction hose	DN 32
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 25 x 4 m
Impulses	100Impulse/l
Suction connection	DN 50
Tap count	1
Accuracy	± 0,5%
Connection suction side	G 1 1/4"

Use the functions on the website to remember or compare

Suction height

3,5m

EQUIPMENT

233400165	Floating switch HDM eco and pro
233400373	Foundation frame HDM eco
2334348001	Suction hose HDM 80 eco Box
233400186	Slanted seat filter for G 1 1/4 for HDM 80 eco Box
233400506	Dispensing hose, with inlay 6.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4
233400508	Dispensing hose 8.00 m DN 25 x 4 instead of 4.00 m DN 25 x 4
233400182	Angle check valve 1 1/4" HDM 80 eco and pro
233400188	Angle check valve 1 1/4" for underground tanks
233400195	Mounting kit return line for HDM eco
233400180	Filter bracket incl. 30 microfilter cartridge
233400300	Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA

Use the functions on the website to remember or compare