



DISPENSING STATION HDM ECO ADBLUE® LZ, INDOOR

UREA **U**

Article number: 110700905

EAN: 4031109005050

DESCRIPTION

Non-calibratable

- With litre counter

Use the functions on the website to remember or compare

- Hybrid pump HORNET W 85 H INOX
- Oval gear meter with pulse generator
- Interface: double pulse
- Type-approved automatic nozzle A 2003 ES, incl. swivel
- Nozzle holder
- Backlit LCD display
- TRbF compliant, incl.drip tray and leak monitoring
- Rear and underground suction pipe connection possible
- Suction line min. DN 32
- Sturdy powder-coated sheet steel housing

* Depending on viscosity and system

TECHNICAL DETAILS

Flow rate	max. 40l/min
Ambient temperature	-7° - +40°C
Medium temperature	-7° - +40°C
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 19 x 4 m
Suction connection female thread	G 1" (BSP)
Tap count	1
Accuracy	± 0,5%
Suction height	4m

Use the functions on the website to remember or compare

EQUIPMENT

233400373

Foundation frame HDM eco

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock