



PUMP SYSTEM HDM 60 ECO BOX LZ

DIESEL **D**

Article number: 110700965

EAN: 4031109005081

DESCRIPTION

- Fuel Management System with PC software (2,000 users)
- Double identification system - driver/vehicle
- Identification via transponder technology
- USB interface to access data
- Rotary pump with single-phase asynchronous motor

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KGMunketoft 42
24937 Flensburg**T** +49 461 8696-126
M sales@tecalemit.demo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- Oval gear meter with pulse generator
- Design-approved A 2010 automatic nozzle, incl. swivel joint
- Discharge hose holder
- Rear and underground suction pipe connection possible
- Suction pipe connection on bottom
- Suction pipe min. DN 32
- Robust powder-coated sheet steel housing
- Two-line illuminated monochrome display, character height 8 or 19 mm
- Stores up to 10,000 tank dispensation data entries
- Menu available in GE, EN, FR, ES, DK, PL, RO, RU
- Additional languages can be installed with a USB flash drive

* depends on viscosity and system

TECHNICAL DETAILS

Flow rate	55l/min
Ambient temperature	-20 - +55°C
Medium temperature	-10 - +35°C
Suction hose	DN 25
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 19 x 4 m
Display	LCD-Digitalanzeige, beleuchtetLCD-Display
Impulses	100Impulse/l
Tap count	1
Accuracy	± 0,5%

Use the functions on the website to remember or compare

Connection suction side

G 1"

Suction height

3,5m

EQUIPMENT

233400165

Floating switch HDM eco and pro

234338003

Suction hose HDM 60 eco Box

233400181

Angle check valve 1" HDM 60 eco

233400187

Angle check valve 1" HDM 60 eco

233400195

Mounting kit return line for HDM eco

233400180

Filter bracket incl. 30 microfilter cartridge

233400300

Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA

Use the functions on the website to remember or compare