



PUMP SYSTEM HDM 60 ECO BOX LZ

Article number: 110700965

EAN: 4031109005081

DIESEL / FUEL OIL



DESCRIPTION

- Fuel Management System with PC software (2,000 users)
- Double identification system - driver/vehicle
- Identification via transponder technology
- USB interface to access data
- Rotary pump with single-phase asynchronous motor

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- Oval gear meter with pulse generator
- Design-approved A 2010 automatic nozzle, incl. swivel joint
- Discharge hose holder
- Rear and underground suction pipe connection possible
- Suction pipe connection on bottom
- Suction pipe min. DN 32
- Robust powder-coated sheet steel housing
- Two-line illuminated monochrome display, character height 8 or 19 mm
- Stores up to 10,000 tank dispensation data entries
- Menu available in GE, EN, FR, ES, DK, PL, RO, RU
- Additional languages can be installed with a USB flash drive

* depends on viscosity and system

TECHNICAL DETAILS

Flow rate	55l/min
Ambient temperature	-20 - +55°C
Medium temperature	-10 - +35°C
Suction hose	DN 25
Power supply (electrical voltage)	230V
Power supply (electrical frequency)	50Hz
Discharge hose	DN 19 x 4 m
Display	LCD-Digitalanzeige, beleuchtetLCD-Display
Impulses	100Impulse/l
Tap count	1
Accuracy	± 0,5%

Use the functions on the website to remember or compare

Connection suction side	G 1"
Suction height	3,5m

EQUIPMENT

233400165	Floating switch HDM eco and pro
234338003	Suction hose HDM 60 eco Box
233400181	Angle check valve 1" HDM 60 eco
233400187	Angle check valve 1" HDM 60 eco
233400195	Mounting kit return line for HDM eco
233400180	Filter bracket incl. 30 microfilter cartridge
233400300	Surcharge fee for Slimline ZVA dispensing nozzle instead of TECALEMIT ZVA

Use the functions on the website to remember or compare