



HDT-DIESEL-ECO-BOX 3 VT 1000 NON CALIBRATABLE

DIESEL 

Article number: 150301064

EAN: 4031109020770

DESCRIPTION

Electric, self-priming vane pump, for diesel, heating oil, and radiator antifreeze (concentrate), GTL, HVO and R33, for use in agriculture, industry, workshops, petrol stations and similar facilities.

Scope of supply:

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Munketoft 42
24937 Flensburg

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- Diesel-Eco-Box 3
- Incl. Vane pump TecPump 600 AC
- Incl. Siphon and return line
- suction filter made of stainless steel (1.4301)
- integrated overflow valve within pump chamber
- Schuko mains plug - cable length 2 m
- Nozzle contact switch for automatic on and off switching of the pump
- Mechanical meter Z 400
- Double walled tank made of PE with galvanized sheet metal jacket
- Level and optical leakage indicator

Technical data:

- Pump type: vane pump
- Medium temperature: -10°C - +40°C
- Ambient temperature: -20°C - +40°C
- Delivery pressure: max. 2 bar
- Delivery volume: max. 55 l/min
- Suction filter: mesh width 0,9 mm

TECHNICAL DETAILS

Flow rate	55l/min
Ambient temperature	-20 - +40°C
Medium temperature	-10 - +40°C
Delivery pressure	2bar
Suction connection	G 1"
Suction height	4m

Use the functions on the website to remember or compare

Connecting thread

G1"

Power supply

370W 4,5A230 V | 50 Hz

EQUIPMENT

252300000

Standard nozzle ZV 2000

234338000

Suction hose for W50II, DN 19 x 4

331000400

Hose DN 19 x 4, G 1 AG, integrated

331000600

Hose DN 19 x 4, G 1 AG, integrated

331000800

Hose DN 19 x 4, G 1 AG, integrated

252620000

Automatic nozzle A 2010

Use the functions on the website to remember or compare