



ELECTRONIC FLOW METER FMT 3 - POM - ADD-ON KIT FOR HORNET 40

Article number: 253591000

EAN: 4031109005319

DIESEL **D**
FUEL OIL
RADIATOR ANTIFREEZE **R**
UREA **U**

DESCRIPTION

- Turbine wheel counter
- For diesel/fuel oil, radiator antifreeze and HVO, GTL, R33

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Munketoft 42
24937 Flensburg

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- Large, illuminated display
- Display 2-line, LED illuminated, 6-digit line, LC-Display with a character height of 16 mm
- Variable display orientation
- Freely rotatable after installation
- incl. HORNET 40 add-on components

TECHNICAL DETAILS

Protection class	IP 65
Max. medium temperature	-10 - +40°C
Nominal pressure	10bar
Viscosity range	0,8 - 40mPa·s
Flow rate min./max.	5 - 120l/min
Bursting pressure	20bar
Subset counter	8
Keypad	3Key(s)
External screw thread	1"
Accuracy after calibration	± 1%
Housing material	POM
Battery	2 x 1,5 V AAA
Battery service life	ca. 5Year(s)

Use the functions on the website to remember or compare

EQUIPMENT

253591997

Attachment kit FMT 3 to HORNET 40

Use the functions on the website to remember or compare