



ELEKTRONIC FLOW METER FMT 3 - PVDF

Article number: 253591200

EAN: 4031109015790

DESCRIPTION

- Turbine wheel counter
- For measuring acids, alkalis and many other non-flammable liquids
- Material wetted parts of measurement chamber: capseld magnetism, PVDF, PTFE, Hasteloy C 22
- Freely rotatable after installation
- Large, illuminated display

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

- Display 2-line, LED illuminated, 4-digit line, LC-Display with a character height of 17 mm

TECHNICAL DETAILS

Protection class	65IP
Nominal pressure	10bar
Viscosity range	0,8 - 40mPa·s
Flow rate min./max.	5 - 120l/min
Bursting pressure	20bar
Accuracy	± 1%
Subset counter	8
Temperature range	- 25 - + 50°C
Keypad	3Key(s)
External screw thread	1"
Housing material	PVDF
Battery	2 x 1,5 V AAA
Battery service life	ca. 5Year(s)

Use the functions on the website to remember or compare