



TECALEMIT FLOW OG 15 BATT | EXTERNAL ANTENNA

Article number: 254510100

EAN: 4031109023313

OIL **O**
RADIATOR ANTIFREEZE **R**

DESCRIPTION

The **TECALEMIT Flow OG 15 Batt | External antenna** is designed for the fast and reliable measurement of high-viscosity media.

At its heart is the high-performance **oval gear measuring chamber (OG 15)**, which ensures precise results for

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

lubricating oils, hydraulic oil, heating oil, diesel fuel, and undiluted coolant/antifreeze. The durable plastic housing of the TECALEMIT Flow and its high **IP65** protection rating guarantee longevity, even under harsh conditions. As part of the Flow system, this meter becomes the central intelligence for your fluid management, automatically capturing, controlling, and analyzing every operation.

TECHNICAL DETAILS

Flow rate	up to 15l/min.
Max. operating pressure	50bar
Protection class	54IP
Connecting thread	See connections below
Viscosity min.	20mPa s
Viscosity max.	2000mPa s
Calibrated accuracy	+/- 0,5%
Uncalibrated accuracy	+/- 1%
Antenna	Connection external LTE & GPS antenna
Power source	Battery - 4x1,5V AA
Measuring chamber	Ovalgear 15
Dimensions	123,3 x 77,5 x 113,7 (LxWxH)mm
Weight	0,75kg

Use the functions on the website to remember or compare

EQUIPMENT

225600005	Antenna LTE/GPS
225600004	Antenne LTE
225600003	Antenna GPS
030498010	RFID Tag Typ 2
030498020	RFID Transponder Card Type 2
030498200	USB RFID Reader For use with PCs
233400203	RFID-TAG Dual Type 1 & 2
233400204	RFID-Card Dual Type 1 & 2

Use the functions on the website to remember or compare