



TECALEMIT FLOW OG 15 AC | INTERNAL ANTENNA

Article number: 254511000

EAN: 4031109023313

OIL **O**
RADIATOR ANTIFREEZE **R**

DESCRIPTION

The **TECALEMIT Flow** is more than just a meter; it's the central intelligence for your fluid management system.

The **TECALEMIT Flow OG 15 AC | Internal Antenna** is engineered for fast and reliable flow measurement of highly viscous media. At its core is the powerful **oval gear measuring chamber (OG 15)**, which ensures precise results for

Use the functions on the website to remember or compare

TECALEMIT GMBH & CO. KG

Am Heizwerk 4
24983 Handewitt

T +49 461 8696-126
M sales@tecalemit.de

mo-th: 08:00 - 16:30 o'clock
fr: 08:00 - 15:00 o'clock

lubricating oils, hydraulic oil, heating and diesel oil, and undiluted coolant. The **robust plastic housing** and high **IP54 protection class** of the TECALEMIT Flow guarantee durability, even under harsh conditions. As an integral part of the Flow system, this meter becomes the central intelligence of your fluid management, automatically recording, controlling, and analyzing all processes. With the **Powerbox AC**, you can power your system and connect external devices such as pumps, external measuring chambers, and probes.

TECHNICAL DETAILS

Flow rate	up to 15l/min.
Max. operating pressure	50bar
Protection class	54IP
Connecting thread	See connections below
Viscosity min.	20mPa s
Viscosity max.	2000mPa s
Calibrated accuracy	+/- 0,5%
Uncalibrated accuracy	+/- 1%
Antenna	Internal LTE & GPS
Power source	Powerbox AC 120 - 230 V 50/60 Hz
Measuring chamber	Ovalgear 15
Dimensions	123,3 x 77,5 x 113,7 (LxWxH)mm
Weight	0,75kg

Use the functions on the website to remember or compare

EQUIPMENT

030498010	RFID Tag Typ 2
030498020	RFID Transponder Card Type 2
030498200	USB RFID Reader For use with PCs
233400203	RFID-TAG Dual Type 1 & 2
233400204	RFID-Card Dual Type 1 & 2

Use the functions on the website to remember or compare